

HCFC, R-22, Mid Point, 60 Hz, 1 - Phase, 115 V

Low Temperature

Production Status: This model is obsolete and is no longer in production for both OEM and service replacement.

Electrical Components

Stator

Resistance:	+-7%	Start Wdg:	2.248	Run Wdg:	0.405
-------------	------	------------	-------	----------	-------

External Protector

Part No. 071-0092-40

Usage Description:

Vendor Name

T I

Capacitor

Part No.	014-0061-05	Low MFD:	430.0
----------	-------------	----------	-------

Type:	Start	High MFD:	516.0
-------	-------	-----------	-------

Usage Description:		Volts:	125
--------------------	--	--------	-----

Capacitor

Part No.	014-0058-10	Low MFD:	430.0
----------	-------------	----------	-------

Type:	Start	High MFD:	516.0
-------	-------	-----------	-------

Usage Description:		Volts:	125
--------------------	--	--------	-----

Capacitor

Part No.	014-0064-08	Low MFD:	40.0
----------	-------------	----------	------

Type:	Run	High MFD:	0.0
-------	-----	-----------	-----

Usage Description:		Volts:	370
--------------------	--	--------	-----

Potential Relays

Part No.	040-0166-21	Usage Description:	
----------	-------------	--------------------	--

Potential Relays

Part No.	040-0166-11	Usage Description:	SPECIAL CUST. APPL.
----------	-------------	--------------------	---------------------