

HCFC, R-22, Mid Point, 60 Hz, 1 - Phase, 208/230 V

High Temperature

**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

**Electrical Components**

<b>Stator</b>					
Resistance:	+-7%	Start Wdg:	4.39	Run Wdg:	1.52

<b>Stator</b>					
Resistance:	+-7%	Start Wdg:	4.64	Run Wdg:	1.48

<b>Internal Protector</b>					
Part No.	071-0432-10				
Usage Description:					
<u>Vendor Name</u>	T I				

<b>Capacitor</b>					
Part No.	014-0061-20	Low MFD:	72.0		
Type:	Start	High MFD:	86.0		
Usage Description:	HIGH TORQUE	Volts:	330		

<b>Capacitor</b>					
Part No.	014-0061-19	Low MFD:	43.0		
Type:	Start	High MFD:	52.0		
Usage Description:	LOW TORQUE	Volts:	250		

<b>Capacitor</b>					
Part No.	014-0064-05	Low MFD:	25.0		
Type:	Run	High MFD:	0.0		
Usage Description:		Volts:	370		

<b>Potential Relays</b>					
Part No.	040-0001-60	Usage Description:			

<b>Potential Relays</b>					
Part No.	040-0166-19	Usage Description:			