

# SRB6-0200-PFV



HCFC, R-22 , 60 Hz, 1 - Phase, V

High Temperature

**Production Status:** This model is obsolete and is no longer in production for both OEM and service replacement.

## Performance

Evap(°F)/Cond(°F)	<u>  </u>	<u>  </u>
RG(°F)/Liq(°F)	<u>  </u>	<u>  </u>
Capacity (Btu/hr):		
Power (Watts):		
Current (Amps):		
EER (Btu/Wh):		
Mass Flow(lbs/hr):		
Sound Power (dBA):	Ave	Max
Vibration(mils(peak-peak)):	Ave	Max

## Mechanical

Number of Cylinders:	CIR (in <sup>3</sup> /Rev):
Bore Size (in):	CFH (ft <sup>3</sup> /hr):
Stroke (in):	
Overall Length (in):	Mounting Length (in):
Overall Width (in):	Mounting Width (in):
Overall Height (in):	Mounting Height (in): *
Suction Size(in):	
Discharge Size (in):	
Initial Oil Charge (oz):	
Oil Recharge (oz):	
Net Weight (lbs):	
HorsePower	
* Overall compressor height on Copeland Brand Product's specified mounting grommets.	

## Electrical

LRA-High*:	UL File No.:	Max Operating Current(Amps):
LRA-Low*:	UL File Date:	MCC (Amps):
LRA-Half Winding:	CSA File No.:	RPM:
RLA(=MCC/1.4; use for contactor selection):		
RLA (=MCC/1.56; use for breaker & wire size selection):		
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.		

## Alternate Applications

<u>Refrigerant</u>	<u>Frequency(Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
--------------------	----------------------	--------------	----------------	--------------------